



# U.S. Department of Labor

## Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

IDENTITY (As Used on Label and List)

**#476s Super Doublecoat Paste Wax**

Occupational Safety and Health Administration  
(Non-Mandatory Form)  
Form Approved  
OMB No. 1218-0072

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

### Section I

Manufacturer's Name

**The Collinite Corporation**

Address (Number, Street, City, State, and ZIP Code)

**Utica, New York 13502**

Signature of Preparer (optional)

Emergency Telephone Number

**315-732-2282**

Telephone Number for Information

**315-732-2282**

Date Prepared: **3-18-2011**

### Section II - Hazard Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity;

Common Name(s))

**Distillates, petroleum, hydrotreated light  
(CAS 64742-47-8)**

Unavailable, 200 ppm\*  
OSHA PEL ACCI/PTLV

Other Limits  
Unavailable  
Recommended % (optional)

\*A TLV has not been established for this product.

### Section III - Physical/Chemical Characteristics

Boiling Point

**Solvent: 360-415 °F**

**Mixture: 428-482 °F**

Solubility in Water

**None**

Appearance & Odor

**Yellow pasty solid, pungent odor**

Specific Gravity (H<sub>2</sub>O = 1)

**0.820**

Vapor Pressure (mmHg)

**Solvent 19.3 @ 100.40 °F**

Vapor Density (AIR = 1)

**Solvent: 5.3**

Melting Point

**132.8-143.6 °F**

Reactivity in Water

### Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used): **140 °F 60 °C Tag closed Cup**

NFPA Class IIIA Combustible Liquid

Flammable Limits

LEL

**1.1%**

UEL

**6.0%**

Extinguishing Media: **Foam, Dry Chemical, CO<sub>2</sub>, Water fog or spray.**

Special Fire Fighting Procedures: **Use air-supplied breathing equipment for enclosed areas. Cool exposed containers with water spray. Avoid breathing vapor.**

Auto-Ignition Temperature: **860 °F 460 °C**

Unusual Fire and Explosion Hazards: **Do not mix or store with strong oxidants like liquid chlorine or concentrated oxygen. Combustible liquid.**

### Section V - Reactivity Data

Stability

Unstable

Conditions to Avoid

Stable **X** **Fires, high temperatures**

Incompatibility (Materials to Avoid)

**Strong oxidants: liquid chlorine, concentrated oxygen, sodium or calcium hypochlorite**

Hazardous Decomposition or Byproducts: **Fumes, smoke and carbon monoxide**

Hazardous                      May Occur                      Conditions to Avoid

Polymerization

Will Not Occur **X** **Does not apply**

## Section VI - Health Hazard Data

|  |   |   |  |
|--|---|---|--|
| <u>Route(s) of Entry:</u>                                  | <u>Inhalation?</u>  | <u>Skin?</u>                                      | <u>Ingestion?</u>                                    |
| <u>Eyes?</u> <b>Avoid-strong irritant, can cause burns</b> | <b>Avoid-causes dizziness, headache, respiratory irritation from dust</b> | <b>Avoid-strong irritant can cause dermatitis</b> | <b>Avoid-do not induce vomiting-call a physician</b> |

Health Hazards (Acute and Chronic)

**Acute: Dizziness, headache, unconsciousness Chronic: Dry skin, skin irritation, dermatitis**

|                         |                    |                         |                        |
|-------------------------|--------------------|-------------------------|------------------------|
| <u>Carcinogenicity:</u> | <u>NTP?</u>        | <u>IARC Monographs?</u> | <u>OSHA Regulated?</u> |
|                         | <b>Unavailable</b> | <b>Not found</b>        | <b>No</b>              |

Signs and Symptoms of Exposure: **Skin erythema, headache, light-headedness**

Medical Conditions Generally Aggravated by Exposure: **dry skin, dermatitis**

Emergency and First Aid Procedures

**If overcome by vapor, remove from exposure, call physician. If ingested, do not induce vomiting. For eye contact, flush with water for 15 minutes.**

## Section VII - Precautions for Safe Handling and Use

Steps to Be Taken in Case Material is Released or Spilled: **Remove all ignition sources. Recover free liquid. Add absorbent (sand, earth, sawdust) Avoid vapors. Ventilate area**

Waste Disposal Method: **Assure conformity with applicable disposal.**

Precautions to Be taken in Handling and Storing: **Keep containers closed when not in use. Do not store near heat, sparks, flame or strong oxidants. Adequate ventilation-equivalent to outdoors.**

Other Precautions: **Avoid breathing vapors. Avoid skin & eye contact.**

## Section VIII - Control Measures

Respiratory Protection (Specify Type)

**Use hydrocarbon vapor canister or supplied air respiratory protection in confined or enclosed spaces.**

|                                     |   |                                   |
|-------------------------------------|---|-----------------------------------|
| <u>Ventilation:</u> <b>Required</b> | <u>Local Exhaust:</u> Face velocity > <b>60 fpm</b> | <u>Special:</u> Adeq. Ventilation |
|                                     | Mechanical(General) explosive proof                 | <u>Other:</u> No smoking, fires   |

Protective Gloves: **Chemical resistant** Eye Protection: **Goggles or face-shield**

Other Protective Clothing or Equipment: **Use chemical resistant apron to avoid repeated/prolonged skin contact**

Work/Hygienic Practices: **Avoid vapors, prolonged skin contact and eye contact. Wash thoroughly after contact. Remove and launder clothing contaminated.**

\* U.S.G.P.O.: 1986 - 491 - 529/45775

THE DATA AND INFORMATION CONTAINED HEREIN ARE BEING FURNISHED FOR INFORMATIONAL PURPOSES ONLY, UPON THE EXPRESS CONDITION THAT EACH CUSTOMER SHALL MAKE ITS OWN ASSESSMENT OF APPROPRIATE USE AND APPROPRIATE SHIPPING, TRANSFER AND STORAGE MATERIALS AND PROCEDURES FOR COLLINITE CORPORATION'S PRODUCTS. ALTHOUGH BASED ON INFORMATION SOURCES WHICH COLLINITE CORPORATION CONSIDERS ACCURATE AND RELIABLE, COLLINITE CORPORATION MAKES NO WARRANTY, EITHER EXPRESS OR IMPLIED, INCLUDING ANY WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, REGARDING THE VALIDITY OF THIS INFORMATION, THE INFORMATION SOURCES UPON WHICH THE SAME ARE BASED, OR THE RESULTS TO BE OBTAINED, AND EXPRESSLY DISCLAIMS LIABILITIES FOR DAMAGES OR INJURIES RESULTING FROM THE USE THEREOF.



This Document has been created with a trial version of deskUNPDF. To purchase a copy of deskUNPDF and remove the trial restrictions, please visit [www.docudesk.com](http://www.docudesk.com) or email [sales@docudesk.com](mailto:sales@docudesk.com) for assistance.